

Industrial Routers

LAN ROUTER

XR5i v2E Series

B+B SMARTWORX

Powered by

ADVANTECH



PRODUCT FEATURES

- Modular design to fit application requirements
- Provided secure connection between two networks
- SNMP protocol for remote management
- 2x ETH, Optional WiFi
- VPN support

The XR5i v2E industrial router secures connections between two local networks (LAN) via two Ethernet interfaces 10/100. WiFi model is available.

Configuration is password protected, via web interface. The router supports creation of VPN tunnels using IPsec, OpenVPN and L2TP to ensure safe communication. Web interface provides detail statistics about router activities.

SELECTED APPLICATIONS

Transportation and security
IT and communication
Self-service terminals
Energy and power industry
Metrology, alarm and warning systems

ORDERING INFORMATION

Note: Check with your local distributor for availability and options. Contact Advantech B+B SmartWorx distributors.

Europe, Middle East, Africa, Asia, South America, Latin America.

BB - XR2 L000 XXX

Accessories	
0	No Accessories
1	Accessories with EU power supply
2	Accessories with UK power supply
3	Accessories with Australia power supply
4	Accessories with US power supply

Enclosure	
1	Plastic enclosure
2	Metal enclosure

0	No WiFi
7	WiFi

ACCESSORIES

ORDER CODE	DESCRIPTION	INCLUDED IN PACKAGE	INCLUDED IN SET PACKAGE	SOLD SEPARATELY
BB-SBD40	Metal DIN holder for Metal versions of routers v2	✓	✓	✓
BB-CPD2-G	Plastic DIN holder for Plastic versions of routers v2	✓	✓	✓
BB-AW-A24G-M5SRP	Antenna WiFi stick 5dB, SMA-RP connector		✓	✓
BB-KD-ETH	Ethernet cross cable 1,5m		✓	✓
BB-CON-WR2	2-pin Terminal block for Power Supply	✓		✓
BB-RPS-v2-WR2-EU	Power supply with WR connector (2 pins) - 12V/1A - EU plug		✓	✓
BB-RPS-v2-WR2-US	Power supply with WR connector (2 pins) - 12V/1A - US plug		✓	✓
BB-RPS-v2-WR2-UK	Power supply with WR connector (2 pins) - 12V/1A - UK plug		✓	✓
BB-RPS-v2-WR2-AUS	Power supply with WR connector (2 pins) - 12V/1A - AUS plug		✓	✓
BB-KN-WR2-3	Power supply cable 2-wire, 3m		✓	✓
Quick Start Guide		✓	✓	

Industrial Routers

LAN ROUTER

XR5i v2E Series



SPECIFICATIONS

FIXED INTERFACES

2x Ethernet	10/100 Mbits, independent or bridged
-------------	--------------------------------------

POWER

Source	9 - 36 VDC
	Idle - 1.6 W
Consumption	WiFi Com. to 1.9 W
	Full Com. to 2.5 W

MECHANICAL

Dimension Plastic version	51 x 87 x 116mm
Dimension Metallic version	42 x 87 x 113mm

Protection	IP30
------------	------

ENVIRONMENTAL

Operating Temperature	-40 to +75°C
Storage Temperature	-40° to +85°C
Humidity	Operating - 0 to 95% relative humidity non condensing Storage - 0 to 95% relative humidity non condensing

WIFI *optional

Antenna connector	R-SMA – 50 Ohms
Supported WiFi band	2.4 GHz
Standards	802.11b, 802.11g, 802.11n
2.4 GHz supported channels	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 11b, 11 Mbps: typ. -85 dBm 11g, 54 Mbps: typ. -70 dBm (HT20) 11n, MSC7: typ. -66 dBm (HT40) 11n, MSC7: typ. -62 dBm 11b, 11 Mbps: min. 18, typ. 19, max. 20 dBm 11g, 54 Mbps: min. 14.5, typ. 16, max. 17.5 dBm 802.11n (HT20): min. 13.5, typ. 15, max. 16.5 dBm 802.11n (HT40): min. 13.5, typ. 15, max. 16.5 dBm
RX Sensitivity	
TX Output Power	
Type of device	Access point, station

CPU & MEMORY

CPU	32b ARM microprocessor, 0.25 DMIPS per MHz
Flash memory	16 MB DDR SDRAM
RAM	64 MB
M-RAM	128 kB

SOFTWARE FEATURES

Linux based, possibility to program your own application

NTP client, NTP Server – time synchronization

M-RAM memory inside – router statistic's saving into memory

NETWORKING

DHCP – automatic IP addressing in LAN network

NAT/PAT – IP address and ports translation between inside/outside network

VRRP – virtual backup router function

DynDNS client – access to the router with a dynamic IP address

PPPoE Bridge – PPP frames encapsulation inside ETH frames

VPN TUNNELING

IPSec, OpenVPN, L2TP – secure encrypted tunnels

CONFIGURATION AND DIAGNOSTIC

HTTP server – configuration via web server

Telnet – configuration and access to the file system

SNMP – router diagnostics, communication with I/O and M-Bus

Remote router group configuration change, switching among configuration profiles

SSH – encrypted configuration and access to the file system

STANDARDS/REGULATION

EMC ETSI EN 301 489-1 V2.1.1, ETSI EN 301 489-17 V3.1.1

Safety EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
+ AC:2011

R-SEENET™

Router Management Software consisting of two parts:

R-SeeNet Server application can be programmed to automatically send SNMP queries (Simple Network Management Protocol) to each router defined in the network. The application retrieves status information from the routers and records it in the SQL database.

R-SeeNet PHP is a web-based application that accesses the SQL database and provides the network administrator detailed information on individual routers and network health.

SMARTWORX HUB™

SmartWorx HUB takes management of your devices to new levels of flexibility and efficiency. Giving you a complete view of your installed device population, SmartWorx Hub delivers invaluable configuration, diagnostic and management facilities directly to your desktop, wherever you are.

Manage a single device or your entire device population at the same time. Whether you need to modify configuration parameters, download or upgrade installed firmware and applications or view detailed information regarding network statistics, you can do it all from any location.