

eXP-S110 PoE Fast Ethernet Extenders

10/100 PoE Ethernet Copper Extenders



- Power remote PoE devices across 2-wire twisted pair or coaxial cable
- Extend 10/100Base-TX up to 10,000 feet (3 KM)
- **On-board PoE power controller** for true compatibility with IEEE 802.3af standard
- High-Speed – up to 200 mbps aggregate line rate
- Transparent operation for all Ethernet protocols including 802.1Q VLAN packets and IP video compression schemes
- **Unique PD Reset feature** enables a central site to reset the **remote PoE device without a truck roll**
- Advanced features: Link Pass-Through*, Interlink Fault Feedback*, Auto-MDIX and Loopback, Plug and Play - Auto configuration of VDSL

Perle **eXP-S110 PoE Fast Ethernet Extenders** transparently extend Ethernet beyond the general limits of 328ft / 100m **while providing Power over Ethernet (PoE)** to standards-based compliant devices such as IP cameras, VoIP phones and wireless access points.

This technology enables users to transparently **extend up to four 10/100 Power over Ethernet connections** across copper wiring. Use single twisted pair (CAT5/6/7), coax or any existing copper wiring previously used in alarm circuits, E1/T1 circuits, RS-232, RS-422, RS-485, CCTV and CATV applications.

At the central site, the 10/100 Ethernet Extender has full PoE support and **operates as a Powered Device (PD)** under IEEE 802.3af supporting end-span and mid-span power sources (PSE). Alternatively, the unit can be powered by the included 48v adapter. The PoE Ethernet Extender at the central site then transmits power over the copper wire to power the remote PoE Ethernet Extender and attached PD. The remote PoE Ethernet Extenders are **classified as Power Sourcing Equipment (PSE)**. While using standard UTP cables that carry Ethernet data, Perle eXP-S110 PoE Ethernet Extenders **provide up to 15.4 watts of power** to Powered Devices (PDs). For longer distance applications the remote PoE Extender (CPE) can be powered by a local 48v adapter. **Learn more about PoE.**

These simple and effective point to point Ethernet Copper Extenders are perfect for commercial buildings, residential units, hospitality environments, and connecting a remote office or private-network backbone to a corporate LAN ... anywhere you need 10/100 Ethernet communication links for PoE devices **up to 10,000ft (3KM) in distance.**

Perle's advanced features such as Link Pass-Through* and Interlink Fault Feedback*, Loopback and remote PD reset*, enable Network administrators to "see everything" for more efficient troubleshooting and less on-site maintenance. These cost and time saving features, along with a lifetime warranty and free worldwide technical support, make Perle Ethernet Extenders the smart choice for IT professionals. **eXP-S110 PoE Fast Ethernet Extenders** are also available with support for **Extended Temperature Environments.**

eXP-S110 PoE Fast Ethernet Extender Features

Extend Ethernet over twisted pair

Extend an Ethernet link over category 5e, 6 and 7 cabling up to 10,000 feet (3 km)

Extend Ethernet over Coaxial cable

Extend an Ethernet link over 75 ohm coaxial cable

On-board PoE Power Controller

As a fully compliant IEEE 802.3af PSE end-span device, this Ethernet Extender's PoE power controller provides compliant power provisioning and monitoring, properly sensing through signature detection whether or not the attach ethernet devices are PoE capable or not. This provides a safe connection for both PoE and Non-PoE capable devices.

Competitive PoE Ethernet Extender products operate as a simple passive power injector and will always apply power to RJ45 port pins which may result in damage if non-PoE compliant Ethernet devices are accidentally attached.

[Click here for more details](#)

Advanced Power capabilities

- ALT A/B and legacy PoE RJ45 pin selection
- Current limiting protection
- Remote PD reset

Fully compliant 802.3af PoE PSE

- Enable/Disable PSE power
- PD signature detection
- Over-Current Protection
- PD power classification detection (Class 0,1,2,3)

Fully Compliant 802.3af/at PoE PD

Only PoE Ethernet Extender solution that provides a Class 0 or 4 signature to PSE for proper operation with PSE equipment such as Cisco PoE switches.

Competitive PoE Ethernet extender solutions cannot be powered by Cisco PoE switches as they cannot provide the necessary PoE PD signature required by the switch. Without this, the switch will not supply power at all.

PSE Status Indicator

A multi-color LED provided presents the status of the PSE function for easy troubleshooting of power over Ethernet connections

PD Power Reset (Port 1)

Ideal for remotely resetting equipment, this configurable function performs a momentary power reset to the attached Powered Device (PD) on Port #1.

Read our **PD Reset Tech Note** for further details on this feature

Power Multiplier Selection

When used with 4-pair cable such as CAT5 on the VDSL Interlink port, an optional internal strap selection on the Ethernet Extender will provide VDSL transmission data on 1 pair and power across the 3 other pairs enabling even greater distances for power transmission to be achieved.

Broadest range of PoE devices supported

Support is included for a broad range of PD (Powered Devices)

- IEEE 802.3af PoE (Alternative A and B)
- Legacy High Capacitance PDs
- Cisco legacy VoIP phones and Wireless Access Points

High-Speed Performance

Utilizes second generation VDSL2 technology (ITU-T Recommendation G.993.). When operating under "Profile 30a", Perle Ethernet Extenders can provide an aggregate VDSL line rate capability of up to 200 mbps.

Actual distance and performance may vary depending on the type / gauge and condition of the wire used and if required, the amount of power you require across the VDSL Link

Plug and Play operation

Perle Ethernet Extenders will automatically configure your VDSL interlink connection. The CO/CPE peer association will be determined automatically by the Ethernet Extender. No need to set CO / CPE VDSL pairing.

Once a connection is made, both ends will automatically adjust relevant VDSL parameters to optimize the level of bandwidth possible across the copper link.

Link Pass-Through

With Link Pass-Through the state of the 10/100Base-TX Ethernet connection is “passed through” the VDSL link to the 10/100Base-TX Ethernet connection on its remote peer. A managed switch on the remote end can then report the state (link up or link down) to its network management system so that any errors can be detected and recovered early.

Competitive Ethernet extenders without this feature will never detect or report any error conditions

Interlink Fault Feedback

Similar to the Link Pass-Through feature, a loss of VDSL link will drop the 10/100 Ethernet port on each end until the link recovers.

Auto-Negotiation

The Ethernet Extender supports auto negotiation on the 10/100Base-TX interface

Auto-MDIX

Auto-MDIX (Automatic Medium-Dependent Interface crossover) detects the signaling on the 10/100 Ethernet RJ45 interface and determines the type of cable connected (straight-through or crossover) and automatically adopts a compatible pinout.

Fixed Speed and Duplex

Some Ethernet equipment require a fixed speed and duplex be used or cannot auto-negotiate. By disabling Auto-Negotiation on the Ethernet Extender, a fixed speed of 10 or 100 mbps as well as Full or half Duplex can be configured through DIP switches.

VLAN

Transparent to tagged VLAN (802.1Q) packets.

Transparent to IP Video compression protocols

Fully transparent to such IP video compression schemes such as MPEG-4, H.264 and MJPEG.

Power Strain Relief strap

A strain relief strap is provided to ensure a solid and secure power connection to the Ethernet Extender. Ideal for areas that may be exposed to vibration.

Loopback

When enabled, will perform a loopback on the copper VDSL Interlink.

*Available on 1 port models.

Specifications

Lifetime limited warranty	Reach, RoHS and WEEE Compliant	HTSUS Number: 8517.62.0020	UNSPSC Code: 43222608	ECCN: 5A991
----------------------------------	---------------------------------------	--------------------------------------	---------------------------------	-----------------------



Remote (Power over Ethernet)

Local (power over link - VDSL)

Power				
Unit Powered by	eXP-1S110E Local power adapter or VDSL	eXP-4S110E Local power adapter or VDSL	eXP-1S110L <ul style="list-style-type: none"> Local power adapter or PoE Power Sourcing Equipment such as a Cisco PoE+ Switch on port #1 PoE+ power injector 	eXP-4S110L <ul style="list-style-type: none"> Local power adapter or PoE Power Sourcing Equipment such as a Cisco PoE+ Switch on port #1 PoE+ power injector
Provides Power to:	eXP-1S110E Ethernet	eXP-4S110E Ethernet	eXP-1S110L Link (VDSL Interlink)	eXP-4S110L Link (VDSL Interlink)
Power adapter connector	Barrel or terminal block			
Input Voltage Range from adapter	eXP-1S110E 46V to 57	eXP-4S110E 46V to 57	eXP-1S110L 29 to 57	eXP-4S110L 29 to 57
Input Voltage Range from VDSL (parasitic)	eXP-1S110E 24 to 57	eXP-4S110E 24 to 57	eXP-1S110L N/A	eXP-4S110L N/A
Universal AC Adapter	48vDC, 60 watts is included when purchased an individual basis. One 48vDC 60 watts adapter is provided in each kit.			
Power Connectors	5.5mm x 9.5mm x 2.1mm barrel socket and 2 pin terminal Block			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	

Ethernet				
10/100Base TX Port(s)	eXP-1S110E 1 port RJ45 Shielded	eXP-4S110E 4 port RJ45 Shielded	eXP-1S110L 1 port RJ45 Shielded	eXP-4S110L 4 port RJ45 Shielded
Auto-MDIX	Auto-MDIX enables proper operation with either straight-through or crossover cabling			
Distance	Distance up to 100 meters (328 feet) as per IEEE 802.3			
Maximum Frame Size	1522			
Type of PoE device	eXP-1S110E PSE (PoE) IEEE 802.3af	eXP-4S110E PSE (PoE) IEEE 802.3af	eXP-1S110L PD (Class 0 or 4 device)	eXP-4S110L PD (Class 0 or 4 device)
PoE PSE Maximum Power (Watts)	eXP-1S110E Refer to the Power Reach Installation Planning Guide	eXP-4S110E Refer to the Power Reach Installation Planning Guide	eXP-1S110L N/A	eXP-4S110L N/A

PoE PSE RJ45 Cable Pinout	eXP-1S110E <ul style="list-style-type: none"> Alternative A (default) on all ports Pins 3,6 Neg, Pins 1,2 Pos Alternative B: selectable on port #1 Pins 7,8 Neg, Pins 4,5 Pos Legacy Cisco Pre-Standard: selectable on port #1 Pins 7,8 Pos, Pins 4,5 Neg 	eXP-4S110E <ul style="list-style-type: none"> Alternative A (default) on all ports Pins 3,6 Neg, Pins 1,2 Pos Alternative B: selectable on port #1 Pins 7,8 Neg, Pins 4,5 Pos Legacy Cisco Pre-Standard: selectable on port #1 Pins 7,8 Pos, Pins 4,5 Neg 	eXP-1S110L N/A	eXP-4S110L N/A
VDSL – Interlink				
RJ45, BNC, Terminal Block	<p>Ethernet Extenders must be connected in pairs using unconditioned wire. Circuits that run through signal equalization equipment are not permitted. TIP and RING are polarity insensitive. Surge suppression of 400 volts between TIP and RING. Choice of RJ45, BNC or terminal block models for VDSL link connector:</p> <ul style="list-style-type: none"> RJ45 – RING pin 4, TIP pin 5 (TIA 568 A/B) BNC – Coaxial 50 and 75 ohm cable with BNC connector Terminal Block – 2 position screw connectors for use with twisted pair telephone, alarm or serial cabling between 19 (0.9 mm) and 26 AWG (0.44 mm). 			

Power Injection over the Interlink (VDSL) – 2-wire	eXP-1S110E N/A	eXP-4S110E N/A	eXP-1S110L Injects SELV compliant voltage and VDSL data across a single pair of cooper wires (pins 4 and 5) or 2 conductor BNC coaxial cable	eXP-4S110L Injects SELV compliant voltage and VDSL data across a single pair of cooper wires (pins 4 and 5) or 2 conductor BNC coaxial cable
Short Circuit Protection	eXP-1S110E N/A	eXP-4S110E N/A	eXP-1S110L Short Circuit protection provided	eXP-4S110L Short Circuit protection provided
Reverse Polarity Protection	eXP-1S110E The voltage from the VDSL link requires proper polarity in order to provide power to the remote extender. Reverse polarity protection however will ensure that there is no damage to the extender	eXP-4S110E The voltage from the VDSL link requires proper polarity in order to provide power to the remote extender. Reverse polarity protection however will ensure that there is no damage to the extender	eXP-1S110L N/A	eXP-4S110L N/A
Power Multiplier Selection	When used with 4-pair cable such as CAT5 on the VDSL Interlink port, an optional internal strap selection on the Ethernet Extender will provide VDSL transmission data on 1 pair and power across the 3 other pairs enabling even greater distances for power transmission to be achieved			

VDSL2 Line Rate/Reach

Actual distance and rates experienced will depend on condition and gauge of wire used. This Rate/Reach table applies to 24 AWG (0.5 MM) twisted pair wiring on RJ45 (RJ) and terminal block (TB) models

High Speed Asymmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	101	92
1000	305	101	63
1500	457	90	38
2000	610	62	24
2500	762	55	10
3000	914	42	5
3500	1000	35	3

High Speed Symmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	101	101
1000	305	85	101
1500	457	62	47
2000	610	60	29
2500	762	44	14
3000	914	30	7
3500	1000	29	4

Long Reach Symmetric

Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	53	44
1000	305	53	43
2500	762	39	18
4000	1219	25	4
5500	1676	17	1.9
7000	2134	8	2.3
7500	2286	7	2.2
8000	2438	5	2.2
Long Reach Asymmetric			
Reach (Distance)		VDSL Rate (Mbps)	
feet	meters	Downstream	Upstream
500	152	78	16
1000	305	78	16
2500	762	55	10
4000	1219	31	0.8
5500	1676	20	0.6
7000	2134	11	0.6
7500	2286	10	0.6
8000	2438	8	0.6

This table applies when the power multiplier option is selected

Power Budget	<p>The amount of available power at the PoE PD is dependent on the scenario planned.</p> <p>Refer to the Power Reach Installation Planning Guide</p>
	<div> <div>Remote (Power over Ethernet)</div> <div>Local (power over link - VDSL)</div> </div>
Indicators	
Power / TST	<p>This green LED is turned on when power is applied to the Ethernet Extender. Otherwise it is off. The LED will blink when in Loopback test mode.</p>
CO - Local	<p>Ethernet Extender is operating in CO VDSL mode</p>
CPE - remote	<p>Ethernet Extender is operating in CPE VDSL mode</p>
ILNK	<p>Indicates Link Status and activity on the Interlink (VDSL) port</p>
ETH	<p>Indicates link status and activity on Ethernet port(s).</p>
PSE Status	<p>This LED will signify the status of the PSE function. Using multi-color and blinking the unit will show the following status for the PSE;</p> <p>GREEN — Solid: The PSE has successfully detected a compliant PD and is applying power over the UTP (for legacy pin out simply show active power when applied)</p> <p>YELLOW — Solid: The PSE is not active. This means the PSE has been configured to provide power, but the PD is :</p> <ul style="list-style-type: none"> • Not connected • Has not detected a compliant PD and is not applying power • PSE has turned off power for Reset function <p>OFF — PSE function switch disabled</p> <p>RED — Blinking: Error Conditions</p> <ul style="list-style-type: none"> • Capacitance too High — 1 blink • Resistance too Low or short circuit — 2 blinks • Resistance too high or open circuit — 3 blinks
Switches	
Access	<p>Switch settings are accessible through a side opening in the chassis</p>

Rate/Reach	Two switches enable the user to select the right balance between speed and distance for their environment.
Signal to Noise Ratio	Selectable Signal to Noise Ratio (SNR) of 6dB or 9dB. The higher SNR number provides better impulse noise protection but lowers performance.
Auto-Negotiation (802.3u)	<ul style="list-style-type: none"> • <i>Enabled (Default)</i> - The Ethernet Extender uses 802.3u Auto-negotiation on the 10/100Base-TX interface. It is set to advertise full duplex. • <i>Disabled</i> - The Ethernet Extender sets the port according to the position of the speed and duplex switches.
Force Ethernet Speed on Port 1	When Auto-Negotiation switch is disabled, a fixed speed can be forced on port 1 to 100 (Default) or 10
Force Ethernet Duplex on Port 1	When Auto-Negotiation switch is disabled, Full or half Duplex can be forced on port 1 to Full (Default) or Half
Link Mode	<ul style="list-style-type: none"> • <i>Standard (Default)</i> - The 10/100Base-TX link remains active independent of the state of the Ethernet link on its remote peer. • <i>Link Pass-Through</i> - state of the 10/100Base-TX Ethernet connection is “passed through” or propagated across the VDSL link to the 10/100Base-TX Ethernet link on its remote Ethernet Extender peer.
Interlink Fault Feedback	<ul style="list-style-type: none"> • <i>Enabled</i> – A loss of VDSL link will drop the 10/100 Ethernet port on each end until the link recovers • <i>Disabled (Default)</i> - The state of the VDSL link is not propagated to the 10/100Base-TX port
Loopback	<ul style="list-style-type: none"> • <i>Enabled</i> – The VDSL interlink will perform a loopback function, retransmitting all received Ethernet frames back to its remote peer. • <i>Disabled (Default - Up)</i>
	Remote (Power over Ethernet) Local (power over link - VDSL)

PoE PD Class selection	eXP-1S110E N/A	eXP-4S110E N/A	eXP-1S110L (Internal strap) for PoE PD classification type identification for attached IEEE 802.3at compliant PoE+ switch on port #1 Class 0 – PoE PD device - 0.44-12.94W (Default) Class 4 – PoE+ PD device 12.95 – 25.5W	eXP-4S110L (Internal strap) for PoE PD classification type identification for attached IEEE 802.3at compliant PoE+ switch on port #1 Class 0 – PoE PD device - 0.44-12.94W (Default) Class 4 – PoE+ PD device 12.95 – 25.5W
------------------------	--------------------------	--------------------------	---	---

PD Reset (Port 1)	<p>eXP-1S110E</p> <p>When enabled (down), the Ethernet Extender will upon loss of link on the VDSL Interlink port, turn off PSE output power to the PD device for 2 seconds then turn the power back on. The power remains on until the VDSL link transitions from up to down again.</p> <p>When PD Power Reset is disabled (default), loss of VDSL link has no effect on power supplied to the PD.</p>	<p>eXP-4S110E</p> <p>When enabled (down), the Ethernet Extender will upon loss of link on the VDSL Interlink port, turn off PSE output power to the PD device for 2 seconds then turn the power back on. The power remains on until the VDSL link transitions from up to down again.</p> <p>When PD Power Reset is disabled (default), loss of VDSL link has no effect on power supplied to the PD.</p>	<p>eXP-1S110L</p> <p>N/A</p>	<p>eXP-4S110L</p> <p>N/A</p>
Environmental Specifications				
Operating Temperature	0°C to 50°C (-32°F to 122°F)			
Storage Temperature	minimum range of -25°C to 70°C (-13°F to 158°F)			
Operating Humidity	5% to 90% non-condensing			
Storage Humidity	5% to 95% non-condensing			

Operating Altitude	Up to 3,048 meters (10,000 feet)			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Current mA	eXP-1S110E 108 @ 48vdc	eXP-4S110E 121 @ 48vdc	eXP-1S110L 129 @ 48vdc	eXP-4S110L 142 @ 48vdc
Unit Power Consumption watts	eXP-1S110E 5.2	eXP-4S110E 5.8	eXP-4S110L 6.2	eXP-1S110L 6.8
Heat Output (BTU/HR)	eXP-1S110E 17.74	eXP-4S110E 19.79	eXP-1S110L 21.16	eXP-4S110L 23.20
MTBF with power adapter (Hours)*	eXP-1S110E 185,061 Hours	eXP-4S110E 169,935 Hours	eXP-1S110L 199,390 Hours	eXP-4S110L 182,735 Hours
MTBF without power adapter (Hours)*	eXP-1S110E 300,472 Hours	eXP-4S110E 262,530 Hours	eXP-1S110L 340,165 Hours	eXP-4S110L 294,389 Hours
	Calculation model based on MIL-HDBK-217-FN2 @ 30°C			
Mounting				
Wall/Desk	Standard			
Din Rail Kit	Optional			
Rack Mount Kit	Optional			
	Remote (Power over Ethernet)		Local (power over link - VDSL)	
Product Weight and Dimensions				
Weight	eXP-1S110E 0.58 Kg, 1.3 lbs	eXP-4S110E 0.61Kg, 1.34 lbs	eXP-1S110L 0.58 Kg, 1.3 lbs	eXP-1S110L 0.61Kg, 1.34 lbs
Dimensions	163 x 116 x 37 mm, 6.4 x 4.6 x 1.46 inches			

	Remote (Power over Ethernet)	Local (power over link - VDSL)
Packaging		
Shipping Weight	eXP-1S110E 1.27 Kg, 2.8 lbs	eXP-4S110E 1.3 Kg, 2.86 lbs
	eXP-1S110L 1.27 Kg, 2.8 lbs	eXP-1S110L 1.3 Kg, 2.86 lbs
Shipping Dimensions	20 x 30 x 7 cm, 7.9 x 11.8 x 2.8 inches	
Regulatory Approvals		
Emissions	<ul style="list-style-type: none"> • CISPR 32:2015/EN 55032:2015 (Class A) • IEC/EN 61000-3-2 • IEC/EN 61000-3-3 	
Immunity	<ul style="list-style-type: none"> • CISPR 35/EN 55035 • IEC/EN 61000-4-2 • IEC/EN 61000-4-3 • IEC/EN 61000-4-4 • IEC/EN 61000-4-5 • IEC/EN 61000-4-6 • IEC/EN 61000-4-8 • IEC/EN 61000-4-11 	
Electrical Safety	<ul style="list-style-type: none"> • UL/EN/IEC 62368-1 • CAN/CSA C22.2 No. 62368-1 • UL 60950-1 • IEC 60950-1(ed 2); am1, am2 • EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013 • CE 	

Product List



eXP-1S110L-RJ - Fast Ethernet PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004224	06004221	06004222	06004225	06004226



eXP-1S110E-RJ - Fast Ethernet PoE Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004584	06004581	06004582	06004585	06004586



eXP-KIT11-S110-RJ Fast Ethernet PoE Ethernet Extender Kit. Includes 1 x eXP-1S110L-RJ PoE ethernet extender, 1 x eXP-1S110E-RJ PoE ethernet extender and 1 x 48V 65W Adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004944	06004941	06004942	06004945	06004946



eXP-1S110L-BNC - Fast Ethernet PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004234	06004231	06004232	06004235	06004236



eXP-1S110E-BNC - Fast Ethernet PoE Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004594	06004591	06004592	06004595	06004596



eXP-KIT11-S110-BNC Fast Ethernet PoE Ethernet Extender Kit. Includes 1 x eXP-1S110L-BNC PoE ethernet extender, 1 x eXP-1S110E-BNC PoE ethernet extender and 1 x 48V 65W Adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004954	06004951	06004952	06004955	06004956



eXP-1S110L-TB - Fast Ethernet PoE Ethernet Extender - Provides power over VDSL Link. 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004244	06004241	06004242	06004245	06004246



eXP-1S110E-TB - Fast Ethernet PoE Ethernet Extender - Provides power over Ethernet as a PSE. 1 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004604	06004601	06004602	06004605	06004606



eXP-KIT11-S110-TB Fast Ethernet PoE Ethernet Extender Kit. Includes 1 x eXP-1S110L-TB PoE ethernet extender, 1 x eXP-1S110E-TB PoE ethernet extender and 1 x 48V 65W Adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004964	06004961	06004962	06004965	06004966



eXP-4S110E-RJ - Fast Ethernet PoE Ethernet Extender - Provides power over Ethernet as a PSE. 4 port 10/100Base-TX (RJ-45). RJ45 Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004704	06004701	06004702	06004705	06004706



eXP-4S110E-BNC - Fast Ethernet PoE Ethernet Extender -Provides power over Ethernet as a PSE. 4 port 10/100Base-TX (RJ-45). BNC Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004714	06004711	06004712	06004715	06004716



eXP-4S110E-TB - Fast Ethernet PoE Ethernet Extender - Provides power over Ethernet as a PSE. 4 port 10/100Base-TX (RJ-45). Terminal Block Interlink (VDSL2) connector. 48V 65W adapter included

Power Cord & Part Number(s)

USA	UK	EU	SA	AUS
06004724	06004721	06004722	06004725	06004726

Related Accessories

Accessories



DIN Rail Mounting Kit for 4 & 8 port IOLAN desktop models, all Stand-Alone Media Converters and all Stand-alone Ethernet Extenders. Two of these brackets are required for the 8 port STS8-D model.

04030840



Standalone media converter wall / rack mount bracket

05059999