

# TN-5900 Series

## EN 50155 16-port NAT routers



### Features and Benefits

- Designed for rolling stock backbone networks
- Dual bypass relay
- Isolated power input range from 24 to 110 VDC
- Complies with all EN 50155 mandatory test items<sup>1</sup>
- -40 to 75°C operating temperature range
- Turbo Ring and RSTP/STP for network redundancy

### Certifications



EN 50155



EN 50121-4



## Introduction

The ToughNet TN-5900 Series, designed for rolling stock backbone networks, are high-performance M12 routers with four bypass relay backbone ports. They support NAT and routing functionality to facilitate the deployment of applications across networks. The TN-5900 Series routers use M12 and other circular connectors to ensure tight, robust connections that guarantee reliability against environmental disturbances, such as vibration and shock.

The TN-5900 Series routers provide a wide power input range of 24 to 110 VDC. TN-5900 Series switches operate in an extended operating temperature range of -40 to 75°C and are compliant with the mandatory requirements of EN 50155/50121-4, making them suitable for a variety of industrial applications.

### Additional Features and Benefits

- Routing functionality to divide a large network into hierarchical subnets and allow data and information to communicate across networks
- NAT makes IP management easier, since end devices in different carriages can use the same IP addresses
- Leading EN 50155 Ethernet router for rolling stock applications
- Turbo Ring and RSTP/STP for network redundancy
- IGMP V1/V2 snooping for filtering multicast traffic
- IEEE 802.1Q VLAN to ease network planning
- QoS (IEEE 802.1p/1Q and TOS/DiffServ) to improve reliability
- Panel mounting or DIN-rail mounting installation capability
- SNMPv3, HTTPS, and SSH to enhance network security
- SNMP v1/v2c/v3 for different levels of network management
- Port mirroring for online debugging
- Automatic warning by exception through email and relay output
- Line-swap fast recovery
- Automatic recovery of connected device's IP addresses
- LLDP for automatic topology discovery in network management software
- Configurable by web browser, Telnet/serial console, and CLI Windows utility

## Specifications

### Input/Output Interface

#### Alarm Contact Channels

2 x relay output in one M12 A-coded 5-pin male connector with current carrying capacity of 1 A @ 30 VDC

1. This product is suitable for rolling stock railway applications, as defined by the EN 50155 standard. For a more detailed statement, click here: [www.moxa.com/doc/specs/EN\\_50155\\_Compliance.pdf](http://www.moxa.com/doc/specs/EN_50155_Compliance.pdf)

## Ethernet Interface

|                                                                             |                                                                                                                                                                                                                                                                                                |
|-----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector)                   | 12                                                                                                                                                                                                                                                                                             |
| 10/100BaseT(X) Ports (M12 D-coded 4-pin female connector with bypass relay) | 4                                                                                                                                                                                                                                                                                              |
| Standards                                                                   | IEEE 802.1D-2004 for Spanning Tree Protocol<br>IEEE 802.1p for Class of Service<br>IEEE 802.1Q for VLAN Tagging<br>IEEE 802.1w for Rapid Spanning Tree Protocol<br>IEEE 802.3 for 10BaseT<br>IEEE 802.3ad for Static Port Trunk<br>IEEE 802.3u for 100BaseT(X)<br>IEEE 802.3x for flow control |

## Ethernet Software Features

|                       |                                                                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration Options | Command Line Interface (CLI), Command Line Interface (CLI) through Serial/Telnet/SSH, Web Browser (HTTP/HTTPS), Windows Utility                                                                |
| Filter                | 802.1Q, IGMP v1/v2, Static Multicast                                                                                                                                                           |
| Management            | Back Pressure Flow Control, DHCP server, Flow control, HTTP, IPv4, LLDP, Port Mirror, QoS/CoS/ToS, RARP, SMTP, SNMP Inform, SNMP Trap, SNMPv1/v2c/v3, Syslog, Telnet, TFTP, Account Management |
| MIB                   | RFC1213                                                                                                                                                                                        |
| Redundancy Protocols  | Link Aggregation, RSTP, Static Port Trunk, STP, Turbo Ring v2                                                                                                                                  |
| Routing Redundancy    | VRRP                                                                                                                                                                                           |
| Security              | Broadcast storm protection <sup>2</sup> , HTTPS/SSL, Local Account Accessibility, TACACS+ <sup>2</sup> , Port Lock, SSH                                                                        |
| Time Management       | NTP Server/Client, SNTP                                                                                                                                                                        |
| Unicast Routing       | Static Route, RIPV1/V2                                                                                                                                                                         |

## Switch Properties

|                   |               |
|-------------------|---------------|
| IGMP Groups       | 256           |
| MAC Table Size    | 8 K           |
| Max. No. of VLANs | 16            |
| VLAN ID Range     | VID 1 to 4094 |

## LED Interface

|                |                                   |
|----------------|-----------------------------------|
| LED Indicators | STATE, PWR1, PWR2, FAULT, 10/100M |
|----------------|-----------------------------------|

## NAT

|          |                                 |
|----------|---------------------------------|
| Features | 1-to-1, N-to-1, Port forwarding |
|----------|---------------------------------|

## Serial Interface

|              |                            |
|--------------|----------------------------|
| Console Port | M12 A-coded male connector |
|--------------|----------------------------|

## Power Parameters

|               |                                                                       |
|---------------|-----------------------------------------------------------------------|
| Input Current | 0.85 A @ 24 VDC, 0.17 A @ 110 VDC                                     |
| Input Voltage | 24/36/48/72/96/110 VDC, Redundant dual inputs, No. of power inputs: 2 |

2. Not supported in FW v1.2.

|                             |                   |
|-----------------------------|-------------------|
| Operating Voltage           | 16.8 to 137.5 VDC |
| Overload Current Protection | Supported         |
| Power Connector             | M23 connector     |
| Reverse Polarity Protection | Supported         |

#### Physical Characteristics

|              |                                                |
|--------------|------------------------------------------------|
| Housing      | Metal                                          |
| IP Rating    | IP54                                           |
| Dimensions   | 250 x 175.8 x 116.3 mm (9.84 x 6.92 x 4.58 in) |
| Weight       | 4,030 g (8.88 lb)                              |
| Installation | DIN-rail mounting (optional), Wall mounting    |
| Protection   | TN-5916-WV-CT-T: PCB conformal coating         |

#### Environmental Limits

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating Temperature                  | -40 to 75°C (-40 to 167°F) |
| Storage Temperature (package included) | -40 to 85°C (-40 to 185°F) |
| Ambient Relative Humidity              | 5 to 95% (non-condensing)  |
| Altitude                               | 2000 m                     |

#### Standards and Certifications

|                         |                                                                                                                                                                                                                                            |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EMC                     | EN 55032/24                                                                                                                                                                                                                                |
| EMS                     | IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV<br>IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m<br>IEC 61000-4-4 EFT: Power: 2 kV; Signal: 2 kV<br>IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV<br>IEC 61000-4-6 CS: 10 V<br>IEC 61000-4-8 PFMF |
| Freefall                | IEC 60068-2-31                                                                                                                                                                                                                             |
| Radio Frequency         | FCC                                                                                                                                                                                                                                        |
| Railway                 | EN 50121-4, EN 50155, IEC 60571                                                                                                                                                                                                            |
| Railway Fire Protection | EN 45545-2                                                                                                                                                                                                                                 |
| Safety                  | IEC 60950-1, UL 61010-2-201                                                                                                                                                                                                                |
| Shock                   | IEC 60068-2-27, IEC 61373, EN 50155                                                                                                                                                                                                        |
| Vibration               | IEC 60068-2-64, IEC 61373, EN 50155                                                                                                                                                                                                        |

#### Declaration

|               |                   |
|---------------|-------------------|
| Green Product | RoHS, CRoHS, WEEE |
|---------------|-------------------|

#### MTBF

|           |                 |
|-----------|-----------------|
| Time      | 556,025 hrs     |
| Standards | Telcordia SR332 |

## Warranty


|                 |                                                                      |
|-----------------|----------------------------------------------------------------------|
| Warranty Period | 5 years                                                              |
| Details         | See <a href="http://www.moxa.com/warranty">www.moxa.com/warranty</a> |

## Package Contents

|                  |                                                                                   |
|------------------|-----------------------------------------------------------------------------------|
| Device           | 1 x TN-5900 Series router                                                         |
| Cable            | 1 x M12-to-DB9 console port                                                       |
| Installation Kit | 2 x cap, female, metal, for M12 port<br>1 x wall-mounting kit                     |
| Documentation    | 1 x document and software CD<br>1 x quick installation guide<br>1 x warranty card |

## Dimensions

Unit: mm (inch)



## Ordering Information

| Model Name      | 10/100BaseT(X) Ports<br>M12 D-Coded 4-Pin Female<br>Connector | 10/100BaseT(X) Ports<br>M12 D-Coded 4-Pin Female<br>Connector with Bypass Relay | Conformal Coating |
|-----------------|---------------------------------------------------------------|---------------------------------------------------------------------------------|-------------------|
| TN-5916-WV-T    | 12                                                            | 4                                                                               | —                 |
| TN-5916-WV-CT-T | 12                                                            | 4                                                                               | ✓                 |

## Accessories (sold separately)

### Storage Kits

|            |                                                                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ABC-01-M12 | Configuration backup and restoration tool with M12 connector for managed Ethernet switches and wireless APs/Bridges/Clients, 0 to 60°C operating temperature |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Cables

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| CBL-M12D(MM4P)/RJ45-100 IP67   | M12-to-RJ45 cable, IP67-rated, 1 m                                         |
| CBL-M23(FF6P)/OPEN-BK-100 IP67 | M23 to 6-pin power cable, IP67-rated female 6-pin M23 connector, IP67, 1 m |

CBL-M12DMM4PM12DMM4P-BK-100-IP67

M12-to-M12 Cat-5E STP Ethernet cable, 4-pin D-coded M12 connector, IP67, 1 m

#### Connectors

M12A-5P-IP68

A-coded screw-in sensor connector, female, IP68, 4.05 cm

M12D-4PMM-IP67

M12 D-coded connector, QUICKON type, 4-pin male, IP67

M12D-4P-IP68

M12 D-coded screw-in sensor connector, male, IP68

A-PLG-WPM23-01-IP67

M23 cable connector, female 6-pin, crimp type, IP67

#### DIN-Rail Mounting Kits

DK-DC50131-01

DIN-rail mounting kit, 6 screws

#### M12 Connector Caps

A-CAP-M12F-M

Metal cap for M12 female connector

A-CAP-M12M-M

Metal cap for M12 male connector

© Moxa Inc. All rights reserved. Updated Nov 12, 2018.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.