

# PCI-1761

8-ch Relay and 8-ch Isolated Digital Input PCI Card



 FCC CE

## Features

- 8 opto-isolated digital input channels
- 8 relay actuator output channels
- LED indicators to show activated relays
- BoardID switch

## Introduction

The PCI-1761 provides 8 opto-isolated digital inputs with isolation protection of 2,500 V<sub>DC</sub> for collecting digital inputs in noisy environments, 8 relay actuators that can be used as a on/off control devices or small power switches.

For easy monitoring, each relay is equipped with one red LED to show its on/off status. Each isolated input supports both dry contact and wet contact so that it can easily interface with other devices when no voltage is present in the external circuit.

## Specifications

### Isolated Digital Input

▪ <b>Channels</b>	8
▪ <b>Input Voltage</b>	Logic 0: 3.0 V max. Logic 1: 10 V min. (50 V max.)
▪ <b>Interrupt Capable Ch.</b>	8 (IDIO ~ IDI7)
▪ <b>Isolation Protection</b>	2,500 V <sub>DC</sub>
▪ <b>Opto-Isolator Response</b>	100 µs
▪ <b>Input Resistance</b>	5.7 k Ohm @ 1 W

### Relay Output

▪ <b>Channels</b>	8
▪ <b>Relay Type</b>	4 x Form C, and 4 x Form A
▪ <b>Contact Rating</b>	2 A @ 250 V <sub>AC</sub> , 2 A @ 30 V <sub>DC</sub>
▪ <b>Max. Switching Power</b>	500 VA, 60 W
▪ <b>Max. Switching Voltage</b>	400 V <sub>AC</sub> , 300 V <sub>DC</sub>
▪ <b>Operating Time</b>	Typical: 7 ms, Max: 15 ms
▪ <b>Release Time</b>	Typical: 2 ms, Max: 6 ms
▪ <b>Resistance</b>	Contact: 100 m Ohm max.
▪ <b>Life Expectancy</b>	2 x 10 <sup>5</sup> cycles min. @ 2A/ 250V <sub>AC</sub>

### General

▪ <b>I/O Connectors</b>	1 x DB37 female connector
▪ <b>Dimensions (L x H)</b>	175 x 100 mm (6.9" x 3.9")
▪ <b>Power Consumption</b>	Typical: 5 V @ 220 mA Max.: 5 V @ 750 mA
▪ <b>Operating Temperature</b>	0 ~ 60°C (32 ~ 140°F)
▪ <b>Storage Temperature</b>	-20 ~ 70°C (-4 ~ 158°F)
▪ <b>Storage Humidity</b>	5 ~ 95 % RH, non-condensing

## Ordering Information

- **PCI-1761** 8-ch Relay and 8-ch Isolated Digital Input PCI Card

### Accessories

▪ <b>PCL-10137-1E</b>	DB37 Cable, 1 m
▪ <b>PCL-10137-2E</b>	DB37 Cable, 2 m
▪ <b>PCL-10137-3E</b>	DB37 Cable, 3 m
▪ <b>ADAM-3937</b>	DB37 DIN-rail Wiring Board