



QSW-M408S

Management Type	Web Managed
Number of Ports	12
10GbE SFP+	4
1GbE (RJ45)	8
Power Supply Description	Adapter
Max. Power Consumption	12.17 W
Input Power Type	AC
Input Voltage Range	100-240VAC, 50/60 Hz
MAC Address Table	16K
Total Non-Blocking Throughput	48Gbps
Switching Capacity	96Gbps
Management Interface	Web
Console (Opt.)	RJ45
Energy Efficient Ethernet (IEEE 802.3az complaint)	Yes
Fan	PWM double ball bearing fan x 1
Supported Standards	IEEE 802.3 Ethernet IEEE 802.3u 100BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3z 1000BASE-SX/LX IEEE 802.3ae 10G Fiber IEEE 802.3x Full-Duplex Flow Control IEEE 802.1Q VLAN Tagging IEEE 802.1w RSTP IEEE 802.3ad LACP IEEE 802.1AB LLDP IEEE 802.3az Energy Efficient Ethernet IEEE 802.1p Class of Service

Form Factor	Desktop
LED Indicators	Per Port: Speed/Link/Activity Per System: Power/Status
Buttons	Reset button
Dimensions (HxWxD)	42.5 × 290 × 127 mm
Weight (Net)	1.145 kg
Weight (Gross)	1.565 kg
Operating Temperature	0°C to 45°C (32°F to 113°F)
Relative Humidity	5~95% Non-condensing
Certifications	CE, FCC, VCCI, BSMI
Electromagnetic Compliance	CLASS A
Jumbo Frames	9K
Warranty	2 Years