



TL-R1200S-RP

Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	2U Rackmount
Host Interface	3 x SFF-8088
LED Indicators	HDD 1-12, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	88.6 × 482 × 562.5 mm
Weight (Net)	9.49 kg
Weight (Gross)	12.77 kg
Max. number of HDDs/SSDs supported	12
Hard Drive Type	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W(x2) PSU, 100 - 240V
Power Consumption: Operating Mode, Typical	73.7 W
Fan Mode Switch	Yes (Auto, high, medium, low)
Fan	2 x 70mm, 12VDC
Sound Level	33.7 db(A)
System Warning	Buzzer

Kensington Security Slot	Yes
--------------------------	-----

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.