

Managed Industrial PoE+ Switch

Features

- Industrial Strength (-40C to +80C Operating Temperature)
- 4 PoE+ or 8 PoE+... and 2 fiber (SFP) Ports
- 10/100/1000 Gigabit Compatible
- Manageable via Console Port or IP
- Surge Protected Voltage and Ethernet Inputs
- Integrated DIN Rail Mount

Applications

- Outdoor Network Installations
- Cameras and Wireless Radios
- Factory networks



TP-SW8G-2SFP 8+2 PoE Switch

Description

The TP-SWxG-2SFP Power over Ethernet (PoE) 6 and 10 port Gigabit switches offered by Tycon® are fully automatic high speed Layer 2+ Ethernet manageable switches. The 6 port model has 4 PoE + 2 SFP ports and the 10 port model has 8 PoE + 2 SFP ports. The PoE ports are Mode A (pins 1,2,3,6) type and are manageable via the user interface. They can be set to PoE, PoE+ or OFF. Default is PoE+.

The switch features security protocols like SSH and SSL for secure access of the switch command interface. The interface can be accessed via the serial console port or any of the Ethernet ports. The command interface can be controlled via web browser, command line interface (CLI), TELNET, SSH or SNMP.

With L2+ features, the switches provide better manageability, security, QOS features and performance. VLAN, Port Mirroring, Port Isolation, IGMP Snooping, DHCP Snooping, LLDP, ARP Inspection, Storm Control, IP Source Guard, Access Control Lists, PoE+ management are just some of the features available with this Industrial PoE Switch.

Spanning Tree, Jumbo Frames, Cable diagnostics, Ring Topology are also supported.

The switches are compliant with 802.3az Energy Efficient Ethernet task force specs. The switch automatically powers down the port Ethernet drivers when a link is not active. Active mode is resumed without loss of any packets when the switch detects the link is active. The switches also automatically adjust the signal strength depending on cable length to save power.

The switches can be powered by 12VDC to 36VDC if no PoE output required or powered from 48VDC to 57VDC if PoE is required.

The units are compatible with Category 5 or higher Ethernet cables with network distances up to 100m. The optical range for fiber ports is up to 20km. The RJ45 connectors are shielded and grounded to the case. The units have surge protection on all ports and are conformal coated for moisture protection. They have a wide operating temperature range for outdoor and industrial applications.



TP-SW4G-2SFP 4+2 PoE Switch

Specifications

	TP-SW4G-2SFP	TP-SW8G-2SFP
Ports	4 Ports 802.3af/at, PoE+ (30W) Mode A 2 SFP/LC Fiber Ports 1 Console Port	8 Ports 802.3af/at, PoE+ (30W) Mode A 2 SFP/LC Fiber Ports 1 Console Port
Transmission Speed	1000 Mbps (Gigabit) / 100 Mbps /10 Mbps Auto-negotiation	
Connections	Shielded RJ45, Shielded SFP/LC, Grounded to Case	
Power Input	Vin 48VDC to 57VDC on Wire Terminal (Max wire size 12AWG) Note: The switch will run on 12V to 36V if no PoE function is needed. For PoE function, the input voltage needs to be at least 48VDC.	
Self Consumption	< 5 watts typical	
LED's	System Power: Blue; Ethernet Link: Amber; PoE: Green; Fiber: Green	
PoE Protections	Over Voltage, Over Current, Short Circuit	
Surge Protection	2kv on Ethernet Ports, 4kv on Power Input	
Management Methods	WEB, CLI, TELNET, SSH, SNMP	
Management Functions	VLAN based on port, VLAN based on 802.1Q, Mirroring, Port Isolation, IGMP Snooping, DHCP Snooping, LLDP, POE+ Management, IP Protection, ARP Inspection and Access Control List, NTP, etc	
Network Protocols and Standards	IEEE 802.3i 10BASET, 802.3u 100BASET, 802.3z 1000BASET 802.3x Flow Control 802.3ab Gigabit Media Independent Interface (GMII) 802.1q VLANs 802.1p (QOS) 802.3ad Link Aggregation Control Protocol (LACP) 802.3af /at (PoE) 802.3az Energy-Saving IEEE G.8032 Ethernet ring protection (<50ms) (STP) 802.1d, (RSTP) 802.1w	
VLANS	Supports up to 4K VLANs simultaneously (out of 4096 VLAN IDs); Port-based VLAN; 802.1Q tag-based VLAN	
IGMP v1/v2 snooping	IGMP limits bandwidth-intensive multicast traffic to only the requesters; supports1024 multicast groups (source-specific multicasting is not supported)	
Network Protections	Port Aggregation, Port Rate Limitation, Broadcast Storm Restraint	
Jumbo Frame Support	9.6K	
Bandwidth	192Gbps (non-blocking)	
Switching Capacity	14.88 mpps @ 64 byte packets	
Packet Forwarding Rate	14.88 mpps @ 64byte packets	
Forwarding Mode	Save and forwarding, link-speed forwarding (Frame Size Range:64~1536)	
Address Table	8K MAC, self-learning	
Operating Temp	-40 to +80°C (-40 to 176°F)	
Operating Humidity (RH)	5% - 95% (non condensing)	
Storage Temperature	-40 to +85°C (-40 to +185°F)	
MTBF	539,608 hours	
Certifications	CE, CE/LVD, FCC, RoHS	
Dimensions (LxWxH)	165*148*54(mm) (6.5 x 5.8 x 2.1")	
Weight	0.9kg (2lb)	
Warranty	5 Years	

System Ordering:

TP-SW4G-2SFP

4 PoE+ and 2 SFP Ports Industrial Managed Gigabit Switch

TP-SW8G-2SFP

8 PoE+ and 2 SFP Ports Industrial Managed Gigabit Switch

For further information contact:

Tyconsystems.com



14641 S 800 W Ste A
Bluffdale, UT 84065
PH: 801-432-0003
FAX: 801-618-4220