

### POE 5 Port Switch

#### Features

- High Power 10/100 and 1000Mb (“G”) PoE Switch
- Remotely Power Equipment thru CAT5 Cable up to 100m
- Up to 2A per Port
- Built-in Surge Protection
- Automatic MDI/MDI-X Crossover
- Automatic Speed and Duplex Sensing
- Compact Size
- High Temperature Operation
- CE and FCC Certification



TP-SSW5-NC



TP-SW5G-D (802.3af/at)  
 TP-SW5G-NC  
 TP-SW5G-MULTI  
 TP-SW5G-24 (802.3af/at)

#### Applications

- Wireless Access Points and Client Devices
- IP Phone and Security Camera Systems

#### Description

The SW5 Series Power Over Ethernet (PoE) switches offered by Tycon Power Systems are fully automatic high speed 5 port Ethernet switches with up to 2A of PoE power per port. The switch comes in 5 models:


**TP-SW5G-D:** IEEE802.3af/at Compliant 48VDC 10/100/1000MB PoE Switch. Switch accepts 48VDC power via a wire terminal connector on the back of the Switch or via 48VDC PoE into the 802.3af/at compliant uplink port (90W max). 35W per port.

**TP-SW5G-24:** IEEE802.3af/at Compliant 48VDC 10/100/1000MB PoE Switch. Switch accepts 12-36VDC power via a wire terminal connector on the back of the Switch or via 48VDC PoE into the 802.3af/at compliant uplink port (90W max). Perfect for remote solar/battery systems. 35W per port.

**TP-SW5G-MULTI:** Universal Multi Voltage 10/100/1000MB PoE Switch. Switch accepts up to 4 different voltages (12-57VDC) so user can power both 48V PoE and 24V PoE devices from the same switch. The port can individually be set to Data Only by disconnecting the voltage input to that specific port. 1A per port.

**TP-SW5G-NC:** Universal Voltage 10/100/1000MB PoE Switch. Switch accepts universal voltage (12-57VDC) via the wire terminal connector on the back of the switch. Also accepts 12-57VDC (1A max) Passive PoE input on port 5. 1A per port.

**TP-SSW5-NC:** Universal Voltage 10/100 PoE Switch. Switch accepts universal voltage (12-57VDC) via the wire terminal connector on the back of the Switch. This model is very compact at only 4”x5”x1.5”. 2A per port.



On the universal voltage models (“-NC”) the PoE output voltage = the input voltage so it is universal in its application. The Ethernet spec supports distances up to 100m (328 feet) between the PoE switch and the remote device.

Tycon Power Systems sells a variety of power supplies in 60W, 120W and 180W sizes. 18VDC, 24VDC and 48VDC are available. All the Switches have DIN Rail mounts included for convenient DIN rail mounting.



## Specifications

	TP-SSW5-NC	TP-SW5G-NC / MULTI	TP-SW5G-D	TP-SW5G-24
<b>Ethernet Standard</b>	IEEE802.3/IEEE802.3u			
<b>Ports</b>	1 data/PoE input and 4 data/PoE, automatic crossover and polarity			
<b>Transmission Speed</b>	100 Mbps /10 Mbps Auto-negotiation	1000Mbps / 100 Mbps /10 Mbps Auto-negotiation		
<b>Switch Technology</b>	Store and Forward			
<b>Protocol</b>	CSMA/CD			
<b>Flow Control</b>	IEEE802.3x(full-duplex), Back Pressure(half-duplex)			
<b>Data Transmission Rate</b>	148800pps ,14880pps	1488000pps for 1000baseT, 148800pps for 100baseT, 14880pps for 10baseT		
<b>Address Table</b>	1K MAC, self-learning			
<b>Connections</b>	Shielded RJ45			
<b>POE Output Ports</b>	Port 1-4, auto power management		Pin assignment: TX(1,2), RX(3,6), V+(4,5), V-(7,8)	
<b>Maximum POE Power</b>	2A per port	1A per port	35W per port	Up to 35W per port; max 70W per 5 port switch
<b>POE Auto Detection</b>	Passive PoE		IEEE 802.3af, 802.3at	
<b>POE Protection</b>	Over Temperature, Over Current, Over/Under Voltage			
<b>Data Surge Protection</b>	IEC61000-4-2 (ESD) ±15kV (air), ±8kV (contact) IEC61000-4-4 (EFT) 40A (5/50ns) IEC61000-4-5 (Lightning) 20A (8/20µs)			
<b>LED's</b>	Link (Green On), Activity (Green Blinking) PoE Detect (Yellow On), PoE Detect Error (Yellow Blinking) Power On (Green On), Power On Alarm (Red On)			
<b>DC Power Input</b>	12V to 57VDC, Dual DC Inputs, Reverse Polarity Protected.	12V to 57VDC, Reverse Polarity Protected. NC Accepts PoE power input on Port 5	48VDC (42V to 60V), Dual DC Inputs, Reverse Polarity Protected. Also Accepts PoE power input on Port 5	24VDC (12V to 36V), Dual DC Inputs, Reverse Polarity Protected. Also Accepts PoE power input on Port 5
<b>Self Consumption</b>	< 1 Watt	< 3 Watts	< 3 Watts	< 4 Watts
<b>Operating Temp</b>	-40 to +85°C (-40 to 185°F)	-20 to +75°C (-4 to 167°F)	-20 to +75°C (-4 to 167°F)	
<b>Operating Humidity (RH)</b>	5% - 90% (non condensing)			
<b>Storage Temperature</b>	-55 to +85°C (-67 to +185°F)			
<b>Dimensions (LxWxH)</b>	90 x 118 x 40mm (3.5 x 4.6 x 1.6")	159 x 118 x 40mm (6.3 x 4.6 x 1.6")		
<b>Weight</b>	182g (6.7oz)	318g (11oz)		383g (13.5oz)
<b>Warranty</b>	2 Years			

### Device Pinouts – TP-SSW5-NC

RJ-45 Port 5 (Data Only)			RJ-45 Port 1-4 (Data & Power)		
Pin	Symbol	Description	Symbol	Description	
1	RX+	Data Receive(+)	RX+	Data Receive(+)	
2	RX-	Data Receive(-)	RX-	Data Receive(-)	
3	TX+	Data Transmit(+)	TX+	Data Transmit(+)	
4	NC	No Connection	+Vdc	DC power(+)	
5	NC	No Connection	+Vdc	DC power(+)	
6	TX-	Data Transmit(-)	TX-	Data Transmit(-)	
7	NC	No Connection	-Vdc	DC power(-)	
8	NC	No Connection	-Vdc	DC power(-)	

### TP-SW5G(-24), TP-SW5G-NC / MULTI

RJ-45 Port 5 (Data & Power)			RJ-45 Port 1-4 (Data & Power)		
Pin	Symbol	Description	Symbol	Description	
1	A+ / +Vdc	Data A+ / DC Power(+)	A+	Data A+	
2	A- / +Vdc	Data A- / DC Power(+)	A-	Data A-	
3	B+ / -Vdc	Data B+ / DC Power(-)	B+	Data B+	
4	C+ / +Vdc	Data C+ / DC power(+)	C+ / +Vdc	Data C+ / DC power(+)	
5	C- / +Vdc	Data C- / DC power(+)	C- / +Vdc	Data C- / DC power(+)	
6	B- / -Vdc	Data B- / DC Power(-)	B-	Data B-	
7	D+ / -Vdc	Data D+ / DC power(-)	D+ / -Vdc	Data D+ / DC power(-)	
8	D- / -Vdc	Data D- / DC power(-)	D- / -Vdc	Data D- / DC power(-)	

### System Ordering: (Note: No Power Supply included)

<b>TP-SW5G-D</b>	5 Port 802.3at/af Gigabit PoE Switch (requires 42-57V DC source)
<b>TP-SW5G-24</b>	5 Port 802.3at/af Gigabit PoE Switch with 12-36VDC input
<b>TP-SW5G-NC</b>	5 Port 12V-56V Gigabit Passive PoE Switch
<b>TP-SW5G-MULTI</b>	5 Port 12V-56V Gigabit Passive PoE Switch with Multi Volt Input
<b>TP-SSW5-NC</b>	5 Port 12V-56V 10/100MB Passive PoE Switch



For further information contact: [Tyconpower.com](http://Tyconpower.com)



14641 S 800 W Ste A  
Bluffdale, UT 84065  
PH: 801-432-0003  
FAX: 801-618-4220