

TPSK Series

DATA SHEET

Solar Kits

Features

- Complete Kit Solar Panel, Pole/Wall Mount, Outdoor 12AWG Cable, Battery Charge Controller
- Accommodates 2" to 4.5" dia. Pole or Wall Mount
- Quick tilt adjustment (15° to 65°)
- Certified for up to 110MPH Winds

Applications

- Remote Power Stations
- Lighting Applications
- Wireless Base Stations
- Surveillance Applications



140W and 280W Kit Mount System

Description

The TPSK series of solar panel kits come complete with high efficiency multicrystalline solar panel, side of pole/wall mounts, PWM Charge Controller and outdoor rated 12AWG cable. They are ready for quick connection to Tycon Power Systems outdoor UPSPro™ Systems or any other application requiring solar power. The panels use only the best silicon cells from Germany to provide excellent low light performance and long life (25years). The rugged aluminum frame and high transparency, low iron, tempered glass withstands high wind, hail and snow loading. The mounts are heavy duty aluminum with stainless steel hardware. They are a simplified design that makes them easy to install, saving precious installer time. The mounts are designed for pole mounting but can also be wall mounted. They provide quick tilt adjustment for positioning the panel to proper sun angles for summer and winter sun.

Specifications

| | TPSK12-30W | TPSK12-70W | TPSK12/24-140W | TPSK12/24-280W |
|---------------------------------|---------------|--------------|-----------------|-----------------|
| Solar Panel Voltage/Capacity | 12V 30W | 12V 70W | 12V/24V 140W | 12V/24V 280W |
| Solar Panel Max Current | 1.74A | 4.07A | 8.14A | 16.28A |
| Solar Panel Size | 20" x 21" | 26" x 30" | 26" x 60" | 52" x 60" |
| Solar Panel Model | TPS-12-30 | TPSHP-12-70 | TPSHP-12-70 x 2 | TPSHP-12-70 x 4 |
| Pole Diameter | 2" to 4.5" | 2" to 4.5" | 2" to 4.5" | 2" to 4.5" |
| Pole Mount Model | TPSM-10-40-SP | TPSM-60-SP | TPSM-70x4-UNI | TPSM-70x4-UNI |
| Wind Speed Rating | 110MPH | 110MPH | 90MPH | 90MPH |
| Charge Controller Model | TP-SC24-20 | TP-SC24-20 | TP-SC24-20 | TP-SC24-20 |
| Cable – 2 Cond – Outdoor | 12AWG x 10' | 12AWG x 10' | 12AWG x 20' | 12AWG x 20' |
| Operating Temperature | -40C to +85C | -40C to +85C | -40C to +85C | -40C to +85C |
| Shipping Weight | 8.2kg (18lb) | 10kg (22lb) | 24kg (53lb) | 36kg (79lb) |

| Solar Kits | Description | Continuous Power with 6 Hours Peak Sun | Continuous Power with 3 Hours Peak Sun |
|----------------|------------------------|--|--|
| TPSK12-30W | 12V 30W Solar Kit | 8W | 4W |
| TPSK24-30W | 24V 30W Solar Kit | 8W | 4W |
| TPSK12-70W | 12V 70W Solar Kit | 17W | 8W |
| TPSK12/24-140W | 12V/24V 140W Solar Kit | 34W | 17W |
| TPSK12/24-280W | 12V/24V 280W Solar Kit | 69W | 35W |







Outdoor Rated Cable

For further information contact:

Tyconpower.com

